

# PRB STYLPROFIL



ORGANIC COATING TO PROTECT

POLYSTYRENE DECORATIVE ELEMENTS

## The PRB STYLPROFIL +

- + Specially formulated to protect polystyrene decorative elements
- + Flexible, strong render
- + Light, smooth appearance
- + Many possible colours for paint finishes
- + Fireproofed formula for better fire behaviour

Ready-to-use



### PACKAGING

- 25 kg plastic tubs.
- 0.4 t pallet, i.e. 16 25 kg tubs.

**STORAGE:** 12 months.

### CONSUMPTION

As an indication: 3 kg/m<sup>2</sup> for a thickness of 2 mm.

**COLOUR:** Off-white

## AREA OF USE

- PRB STYLPROFIL is a ready to use fire-proofed mortar.
- Direct application onto the polystyrene substrate without requiring any additional reinforcement.
- PRB STYLPROFIL must be covered using acrylic (PRB COLOR ACRYL FLEX) or siloxane (PRB COLOR SILOFLEX) paint when exposed outdoors.

## TECHNICAL SPECIFICATIONS

### COMPOSITION

- Aqueous dispersion of polymers, mineral fillers, fire-proofing fillers, specific additives.

### SPECIFICATIONS

- Density: 1.5 ± 0.05
- pH: 8.5

### PERFORMANCES

- Fire behaviour - ignition test as per EN ISO 11925-2: no ignition (REPORT CSTB RA16-0301).

## PREPARATION

### APPLICATION

- Important: Mix using an electric mixer before use.
- Application in layers 2 to 5 mm thick.
- Drying time: 48 to 75h for a 2 mm thickness.
- Drying in a ventilated room at a temperature regulated to at least 18°C.

### PRECAUTIONS FOR USE

- Refer to the regulatory labels on the packaging and to the safety data sheet before use.
- Comply with applicable regulations.

PRB STYLPROFIL  
ORGANIC COATING TO PROTECT  
POLYSTYRENE DECORATIVE ELEMENTS

E.V.I.